

Description

L-20™ Lubricant is a biodegradable vegetable oil based lubricant with a uniquely high affinity for coating particles in the drilling fluid, well bore and metal surfaces. It is recommended for use whenever friction contact is anticipated. Recommended treatment include running 2-10 bbl pills or by addition of 2-3 percent by volume to the system.

Typical Performance

- Superior lubricity
- Exceptional film strength
- High affinity for metal and particle surfaces
- Environmentally friendly
- Minimizes torque and drag

Applications

- Designed to reduce drag on all surfaces
- Works in all WBM's including salt systems
- Very effective in gumbo inhibition
- Effective performance enhancer for Water Based Systems

Safety: Always refer to the Safety Data Sheet for detailed information on shipping, handling, storage, and use.

Important: The information provided herein is believed to be accurate and reliable, but is presented without guarantee on the part of ViChem. Further, nothing contained herein shall be taken as an inducement to violate any patent rights.

Packaging, Handling & Storage

- Packaging: 55 gal. drum, 5 gal bucket. Prices vary upon packaging type.
- Non Toxic and Biodegradable.
- Storage: 6 months in original unopened drums/IBC between 5°C (41°F) and 40°C (104°F). Protected from freezing.

Physical Properties

Type:	Lubricant
Appearance:	Brown Viscous Liquid
Odor:	Bland
Temperature Stability:	Up to 16 hrs. @ 300°
Specific Gravity:	~1.04 – 1.06
pH:	3.5 - 4.5
See Also MSDS	